

The Natural Collection  
**HEX XL ECOSTONES**

ø 51,60 mm (2")

■ **SUITABILITY AREA PRODUCT & COMPOSITION GUIDE**

| REFERENCE    | WALL      | FLOOR       | WET AREAS | POOLS | MATERIAL |
|--------------|-----------|-------------|-----------|-------|----------|
| All Products | Int / Ext | Residential | Yes       | Yes   | Glass    |

■ **TECHNICAL CHARACTERISTICS**

| TEST<br>UNE-EN-ISO 10545-3<br>WATER ABSORPTION           | TEST<br>UNE-EN-ISO-101-92=101<br>SURFACE HARDNESS.<br>MOHS. | TEST<br>UNE-EN-ISO 10545-9<br>RESISTANCE TO<br>THERMAL SHOCKS        | TEST<br>UNE-EN-ISO 10545-12<br>FROST<br>RESISTANCE                   | TEST UNE-EN-ISO 10545-13:1998 RESISTANCE TO CHEMICAL ATTACK |  |   |                           |
|--|---|--|--|---|--|---|---------------------------|
|  |   |  |  | DOMESTIC PRODUCTS   | POOL WATER<br>ADDITIVES                      | LOW ACID AND<br>ALKALINS  | HIGH ACID AND<br>ALKALINS |
| None   | 4   | Resistant  | Resistant  | GA  | GA   | GLA   | GHA                       |
| TEST<br>UNE-EN-ISO 10545-14<br>RESISTANCE<br>TO STAINING | TEST<br>UNE-EN-ISO 10545-<br>11=1997<br>CRACKING            | DIN 51094<br>COLOUR STABILITY ON<br>EXPOSURE TO LIGHT<br>AND UV RAYS | DCOF<br>WET DYNAMIC COEFFICIENT OF FRICTION<br>ANSI A 137.1 STANDARD | DIN 51130:2004<br>SLIP RESISTANCE<br>WEARING SHOES          | DIN 51097<br>SLIP RESISTANCE IN<br>BARE FEET | TEST UNE-ENV<br>12633:2003 (CTE) ANTI<br>SKID COEFFICIENT,<br>SUITABLE FOR<br>OUTDOOR USE AND<br>SWIMMING POOLS |                           |
| Class 5  | Resistant   | Resistant  | > 0,60*  | R11*  | Class C*                                     | Class 3*  |                           |

\*Matte products

■ **PACKING**

| SHEET<br>HOJA                                   | BOX<br>CAJA   | PALLET<br>PALET  | EURO PALLET<br>EURO PALET                                  |
|---|---|--|--|
| Size / Dimensión:<br>286x284 mm (11.25"x11.18") | Sheets / Hojas:<br>6                                    | Quantity / Cantidad:<br>88,20 m <sup>2</sup> (949.37 sqft) | Quantity / Cantidad:<br>58,80 m <sup>2</sup> (632.91 sqft) |
| Thickness / Espesor:<br>5,3 mm (0.173")         | Quantity / Cantidad:<br>0,49 m <sup>2</sup> (5.27 sqft) | Boxes / Cajas:<br>180                                      | Boxes / Cajas:<br>120                                      |
| Weight / Peso:<br>0,921 Kg (2.03 lb)            | Weight / Peso:<br>5,524 Kg (12.17 lb)                   | Gross weight /<br>Peso bruto: 1014,32 Kg<br>(2236 lb)      | Gross weight /<br>Peso bruto:<br>682,88 Kg (1505.49 lb)    |



Minimum  
Order  
1 module / 1 Box



Sales  
Unit  
Square meters



Mosaic  
Support  
MESH

All ONIX 98 % recycled glass mosaics series are made of molten glass. Molten glass characteristics may include irregular edges and small variations in size. These characteristics are inherent to the product and to the standard production. The small size and shape variations can affect the grout joint appearance and enhance the natural aspect of these products.