

## SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

REFERENCE	WALL	FLOOR	WET AREAS	POOLS	MATERIAL
All Products, except Matte	Int/ Ext	No	Yes	No	Glass Metals
Habana Matte, Neon Matte, Honey Matte, Fosco Matte, Ivy Matte	Int/ Ext	Residential	Yes	Yes	Glass

## TECHNICAL CHARACTERISTICS

TEST UNE-EN-ISO 10545-3 WATER ABSORPTION	TEST UNE-EN-ISO-101-92=101 SURFACE HARDNESS. MOHS.	TEST UNE-EN-ISO 10545-9 RESISTANCE TO THERMAL SHOCKS	TEST UNE-EN-ISO 10545-12 FROST RESISTANCE	TEST UNE-EN-ISO 10545-13:1998 RESISTANCE TO CHEMICAL ATTACK			
				DOMESTIC PRODUCTS	POOL WATER ADDITIVES	LOW ACID AND ALKALINS	HIGH ACID AND ALKALINS
None	4	Resistant	Resistant	GA*	GA*	GLA*	GHA*
TEST UNE-EN-ISO 10545-14 RESISTANCE TO STAINING	TEST UNE-EN-ISO 10545- 11=1997 CRACKING	DIN 51094 COLOUR STABILITY ON EXPOSURE TO LIGHT AND UV RAYS	DCOF WET DYNAMIC COEFFICIENT OF FRICTION ANSI A 137.1 STANDARD		DIN 51130:2004 SLIP RESISTANCE WEARING SHOES	DIN 51097 SLIP RESISTANCE IN BARE FEET	TEST UNE-ENV 12633:2003 (CTE) ANTI SKID COEFFICIENT, SUITABLE FOR OUTDOOR USE AND SWIMMING POOLS
Class 5	Resistant	Resistant	≥ 0,42*		R11*	Class C*	Class 3*

## PACKING

SHEET HOJA	BOX CAJA	PALLET PALET	EURO PALLET EURO PALET
Size / Dimensión: 311x311 mm (12.24"x12.24")	Sheets / Hojas: 5	Quantity / Cantidad: 105,84 m <sup>2</sup> (1,139 sqft)	Quantity / Cantidad: 70,56 m <sup>2</sup> (759.5 sqft)
Thickness / Espesor: 4,9 mm (0.19")	Quantity / Cantidad: 0,49 m <sup>2</sup> (5.27 sqft)	Boxes / Cajas: 216	Boxes / Cajas: 144
Weight / Peso: 0,91 Kg (2.01 lb)	Weight / Peso: 4,57 Kg (10.1 lb)	Gross weight / Peso bruto: 987,12 Kg (2,175 lb)	Gross weight / Peso bruto: 658 Kg (1,450 lb)



Minimum  
Order  
1 module / 1 Box



Sales  
Unit  
Square meters



Mosaic  
Support  
MESH



Mosaic  
Support  
DOTS

All ONIX 98 % recycled glass mosaics series are made of molten glass. Molten glass characteristics may include irregular edges and small variations in size. These characteristics are inherent to the product and to the standard production. The small size and shape variations can affect the grout joint appearance and enhance the natural aspect of these products.

# GLASS METALS INFORMATION

ES

## INSTRUCCIONES COLOCACIÓN Y PRECAUCIONES

### ATENCIÓN, MANIPULAR CON MUCHO CUIDADO

Dado su acabado especial, adoptar las mismas precauciones para su conservación que en un recubrimiento de oro, bronce o plata.

### ADVERTENCIAS DE COLOCACIÓN:

Para su colocación utilizar una llana de goma, y evitar a toda costa, el contacto con las piezas contiguas.

Se aconseja emplear junta de rejunte tipo 0-5 para evitar abrasión.

Limpiar con una esponja fina ligeramente humedecida en sentido diagonal a la trama de juntas.

No emplear lijas, espantos o esponjas ásperas.

No utilizar productos de limpieza abrasivos, y/o de Ph ácido básico, a excepción del amoniac diluido y vinagre. No mezclar con agua sucia o salobre.

En zonas húmedas como spas, piscinas de uso público, donde se utilizan productos salinos y/o desinfectantes agresivos como la lejía, no se aconseja su colocación.

EN

## INSTRUCTIONS FOR INSTALLATION & CARE

### WARNING, HANDLE WITH DE MAXIMUM CARE

Given their special finish, the same precautions apply to these products as those used when caring for gold, copper or silver coverings.

### PRECAUTIONS WHEN LAYING THE TILES:

Use a rubber mallet to lay them. Under no circumstances should adjoining tiles come into contact with one another.

Use a slightly damp sponge to clean the tile joints, passing it diagonally across them. Do not use dirty or brackish water. Do not use sandpaper or rough sponges.

Do not use abrasive, acidic or alkaline cleaning products, except for diluted ammonia and vinegar.

We recommend the use of 0-5mm grout joint type to avoid abrasion.

These products are not suitable for wet areas like public spas or swimming pools where aggressive saline and/or disinfectant products like bleach are used.

FR

## CONSEILS RELATIFS À LA POSE ET À L'ENTRETIEN

### ATTENTION, TRAITER LE PRODUIT AVEC LE PLUS GRAND SOIN.

En raison de sa finition spéciale, le produit doit être entretenu en adoptant les mêmes mesures de précautions que pour un revêtement en or, en bronze ou en platine.

### AVERTISSEMENTS CONCERNANT LA POSE:

Pour une pose correcte, employer un maillet en caoutchouc et éviter à tout Prix le contact avec les pièces contiguës.

Nettoyer avec une éponge fine légèrement humidifiée et en diagonale par rapport aux joints. Ne pas mélanger avec de l'eau sale ou saumâtre. Ne jamais utiliser le papier de verre, le sparte ou l'éponge abrasive.

Ne pas employer des produits de nettoyage abrasifs ou à pH acide ou basique, à l'exception de l'ammoniac dilué et du vinaigre.

Il est conseillé d'utiliser un produit de joint de type 0-5 pour éviter l'abrasion.

La pose est déconseillée dans les zones humides telles que les spas ou les piscines à usage public, où sont employés des produits salins et/ou désinfectants agressifs tels que l'eau de javel.